




PAINT/GASKET REMOVER

**SPECIALTY
MAINTENANCE
PRODUCTS**



SPRAYON[®] HEAVY DUTY PAINT REMOVER

- Fast-acting paint remover
- Removes baked finishes
- Cuts through all paint finishes, urethanes, varnishes and shellac
- Leaves surface clean and ready to repaint



CLEANERS, DEGREASERS
LUBES AND SEALANTS

SUPERIOR
LUBRICANTS

PAINTS, COATINGS
AND PRIMERS

CAULKS, SEALANTS
AND ADHESIVES

BRUSHES, ROLLER COVERS
AND ACCESSORIES

Sprayon[®] Heavy Duty Paint is a fast-acting remover that cuts through all paint finishes (air-dry or baked). It also removes urethane, varnish and shellac. Its catalyst action penetrates through gasket cements, decals, sealants, adhesives, tape residue and carbon deposits. NSF registered for use in meat and poultry plants.



Distributed by Rhino Marking & Protection Systems • 800-522-4343 • www.RhinoMarkers.com



PROPERTIES

BASE TYPE: Methylene Chloride
APPEARANCE: Translucent White
ODOR: Chlorinated
PROPELLANT: Hydrocarbon
ACTIVES: 62.00%
WT/GAL.: 7.74
SPECIFIC GRAVITY: 0.93
HAZARD CODE: 2,3,0
VOC: 33.30%
OTC & CALIFORNIA COMPLIANT: Yes
FLAMMABLE: Yes
FLASH POINT: < 0°F

PERFORMANCE

- NSF Registration Number 115076; C3 Rated
 - Removes adhesives and backed-on gaskets
 - Leaves surface ready to paint or decorate.
 - Removes lacquer, enamels, graffiti* (see note), varnish, shellac, baked on coatings, labels and decals.
 - NOTE: S00615 is damaging to plastic, fiberglass or any synthetic materials. User accepts all responsibility for such use. Do not allow to dry on surface.
- SHELF LIFE: 3 years from date of manufacture

USES

- Metal
- Stone
- Wood
- Brick
- Glass
- Ceramic tile
- Concrete
- Road signs
- Trucks
- Bridges
- Washroom walls
- Transportation and construction equipment
- All types of general maintenance

APPLICATION

Use in a well ventilated area. Shake can for 1 minute. Protect surrounding areas from overspray. Wear rubber gloves, face & eye protection. Spray heavy coat with a steady back and forth motion keeping spray upright 8-10" from surface. Allow product to penetrate into paint finish or gasket cement. WATCH for the following: SOFTENING: Approximately 10 minutes. BLISTERING: Approximately 20-30 minutes. A second application might be necessary. When chemical action is complete, scrape off with flexible putty knife or squeegee. Rinse thoroughly with solvent or water wash. Allow surface to dry completely before applying a new finish. Prime metal as soon as possible to prevent rust. For best results, use at room temperature (70°F-90°F).

PACKAGING

Stock #: S00615
UPC Code: 0-75577-90615-4
Fill Wt.: 15 oz.
Per Case: 12
Carton Dimensions:
L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:
www.KPG-Industrial.com
CUSTOMER SERVICE:
1-800-777-2966
TECHNICAL INFORMATION:
1-800-251-2486

Distributed By:

Rhino Marking & Protection Systems
280 University Drive, Waseca, MN 56093
Customer Service: 800-522-4343
Damage Prevention Specialists: 866-622-4343
www.RhinoMarkers.com
* A division of REPNET, Inc.



Nonfood Compounds
Program Listed (C3 Rated)
(Registration #115076)



Krylon Products Group
101 Prospect Ave. NW
Cleveland, OH 44115
www.KPG-Industrial.com
Tel: 1-800-777-2966